


Simulation study on ELT time transfer

Stefan Marz, Anja Schlicht, Christoph Bamann

Technical University of Munich

Forschungseinrichtung Satellitengeodäsie (FESG)

30th June 2017



Uhrenturm der TUM


Introduction

- Aim of ELT: Establishing of an optical time transfer between SLR station clocks and the ACES clock with picosecond accuracy.
- A Classical two-way (round trip) and an additional one-way optical link shall be established, based on timing via ultra-short laser pulses
- Space based ELT hardware: Single photon avalanche diode (SPAD), corner cube retro-reflector (CCR) and an event timer connected to the ACES time scale




Principle of ELT

Optical link:



Microwave link:



One and two way signal time of flight

- One way:

$$tof = R_{tr} + \tau_{troposphere} + \tau_{Sagnac} + \tau_{Shapiro} + \tau_{attitudeDetector}$$

- Two way:



$$tof = 2 * (R_{tr} + \tau_{troposphere} + \tau_{Shapiro} + \tau_{attitudeReflector}) + \tau_{Reflector}$$

with R_{tr} : Distance between space and ground station references

Simulation and evaluation program

- Input: Simulated ISS orbit data as predictions
- Possibility to add disturbances in radial, along-track and cross-track direction
 ➡ true orbit
- Customizable parameters (for instance):
 - one- and two-way detection probability
 - detector gate width
 - background noise rate
 - laser pulse length and detector parameters
 - repetition rate of the laser
 - satellite body rotation
 - detector and reflector offsets relating to center of mass
 - clock offset and noise
 - station specific parameters (e.g. station range bias and meteorological data)

Simulation of the ACES clock



Simulation and evaluation program

- Evaluation work flow:
 - Two-way ranging
 - Correction of orbit disturbances

- One-way ranging
- Filtering of ELT detector residuals
 - Exponential fit
 - Pre-filtering around 1 ns
 - Gaussian curve according to 2,3 σ



- Calculating data triplets

Simulation and evaluation of background noise

Background noise rate [1/s]:

$5 * 10^6$

$1 * 10^7$





Simulation and evaluation of background noise

Background noise rate [1/s]:



$2,5 * 10^7$

$5 * 10^7$





Simulation and evaluation of orbit disturbances

- Along-track error 2 m





Simulation and evaluation of orbit disturbances

- Along-track error 20 m




Simulation and evaluation of orbit disturbances

- Along-track error 50 m




Laser pulse length

20 ps





100 ps







One-way ranging and filtering

- Background noise rate: $1 * 10^7 \frac{1}{s}$
- Along track error: 50 m
- Laser pulse length: 20 ps





One-way ranging and filtering

- Detector residuals pre-filtering: Exponential fit and cutting around 1 ns




One-way ranging and filtering

- Gaussian curvature: Filtered residuals according to $2,3 \sigma$



Data triplets




Summary

- Correction of orbit disturbances works quite well
- For larger pulse lengths the orbit correction becomes worse
- For a to flat background noise no exponential fitting
- For a to large background noise the peak disappears in noise
- Filtering provides the signal quite well (using 2,3 σ)
- Optimal case assumed

Outlook:

Single photon mode and multi-photon peak

- High precision photon arrival time tagging (very important in time transfer)
- High background photon flux
- With multi photons the accuracy is limited due to time walk effect



Thank you!